

## **RECHARGEABLE LED SPOTLIGHT - CERTIFIED IP67**



## 889 RT

## PROMO

- Ideal for illuminating wide working areas
- Can be used both indoor and outdoor
- Resistant to water, dust and chemicals
- Shock resistant
- Double mode operation: with or without cable
- Up to 8 hours of use in cordless mode
- 3 selectable brightness levels
- High resistance reinforced structure
- Magnetic base adjustable up to 180°
- Can be mounted on the tripod
- Supplied with 5 m charger cable, with warning light (red: charging in progress, green: charge complete)
- Spare battery charger: code 1004732-64

Type and number of LED	1 x 10.6W COB LED
Operating temperature (°C)	-10 ÷ 40
Protection level	IP67
Color Rendering Index (CRI)	85
Beam angle	120°
Light beam distance (m)	26-37-45
Recharge time (hours)	2,5
Autonomy min-max (hours)	2,5-4-8
Battery type (supplied)	11,V Li-Ion 2600 mAh
Shock resistance	IK07
Battery charger (OUTPUT)	DC 12.6V 1.3A

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB) Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia Partita IVA e C.F: 03225990138 StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc. Capitale Sociale I.V. € 12.000.000



Light flux (lm)	500-1000-1500
Battery charger (INPUT)	AC 100-240V 50/60HZ 0.5A
Light intensity (lux@0,5m)	690-1390-2030
N° lighting modes	3

## Family details

Code	LxPxH mm	Weight kg	
U08890038	160x63x130	2	1

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB) Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia

Partita IVA e C.F: 03225990138



Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000