

LED INSPECTION LAMP



889 RD

- Dual use: inspection lamp or torch
- Magnetic base adjustable up to 180°
- Two rear magnets
- Two retractable hooks that can be rotated 360 °
- Check of charge status with warning light on lamp body (red: charging in progress, green: charge complete)
- Supplied with battery charger and cigarette lighter cable

Light source (lamp function)	6 x SMD LED
Operating temperature (°C)	-20 ÷ 60
Protection level	IP20
Beam angle	60°
Color Rendering Index (CRI)	80
Color temperature (k)	6500
Recharge time (hours)	4,5
Autonomy: lamp-torch (hours)	5-9
Battery type (supplied)	3,7 V Li-Ion 2400 mAh
Shock resistance	IK07
Battery charger (OUTPUT)	6VDC 500mA
Light flux: lamp-torch (lm)	200-50

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
 Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
 Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc.
 Capitale Sociale I.V. € 12.000.000

Battery charger (INPUT)	230-240 VAC 50Hz 5.0W
Light intensity: lamp-torch (lux@0,5m)	300-450
Light source (torch function)	1 x 3W SMD LED

Family details

Code	L mm	 Weight gr	 Quantity for packaging
U08890035	250	260	1

Spare parts

Articles



889 UC - Spare charger 230 V