

COMPACT LED RECHARGEABLE INSPECTION LAMP



889 RP

PROMO

- Dual use: inspection lamp or torch
- Magnetic base adjustable up to 180°
- Retractable hook that can be rotated 360°
- Belt hook
- Check of charge status with warning light on lamp body (red: charging in progress, green: charge complete)
- Supplied with wall type charger with USB output

Light source (lamp function)	1 x 2,5 W COB LED
Operating temperature (°C)	-20 ÷ 50
Color Rendering Index (CRI)	80
Color temperature (k)	6500
Light beam distance: lamp-torch (m)	5-10
Beam angle	120°
Recharge time (hours)	4,5
Autonomy min-max (hours)	3-10
Battery type (supplied)	3.7V Li-Ion 1800 mAh
Battery charger (OUTPUT)	DC 5V 1000 mA
Light intensity (lux@0,5m)	220-90
Battery charger (INPUT)	AC 100-240V 50/60HZ

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000

Le informazioni e le immagini qui contenute sono soggette a continuo aggiornamento: tali dati sono pertanto da ritenersi indicativi e suscettibili di eventuali errori e/o imprecisioni. Stanley Black & Decker Italia S.r.l. declina ogni responsabilità circa le informazioni e le indicazioni ivi contenute.

Protection level	IP20
Light flux: lamp-torch (lm)	180-60
Light source (torch function)	3 x SMD LED

Family details

Code	LxPxH mm	 Weight gr	 Quantity for packaging
U08890045	131x31x62	140	1

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo
da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000