

Made in Italy

WORKBENCHES



WORKBENCHES 506 TA

WITH STEEL TOP









Workbench with steel worktop

- Galvanized steel worktop 3 mm thickness.
- 37 mm edges to prevent objects from falling.
- Metal sheet legs and bottom shelf 1,2 mm thickness.
- · Structure painted in colour black RAL 9005.
- Side holes to fix several workbenches side by side.
- · Arranged for ground fixing.
- 6 legs for 2 meters lenght model.
- Possibility to assemble the drawer 506 TC1.
- · Static load resistance: 2000 kg.
- Space in between legs: 864 mm.
- Space in between bottom shelf and worktop: 570 mm.



Steel worktop 3 mm thickness.



37 mm edges.








506 TAC U05060156





Workbench with steel worktop - 2 drawers

- 2 drawers included with internal dimensions 834x550x130 mm.
- Drawers mounted on telescopic slides with static load up to 60 Kg.
- Galvanized steel worktop 3 mm thickness.
- 37 mm edges to prevent objects from falling.
- Metal sheet legs and bottom shelf 1,2 mm thickness.
- Structure painted in colour black RAL 9005.
- Side holes to fix several workbenches side by side.
- · Arranged for ground fixing.
- 6 legs for 2 meters lenght model.
- Possibility to assemble the drawer 506 TC1.
- Static load resistance: 2000 kg.
- Space in between legs: 864 mm.
- Space in between bottom shelf and worktop: 570 mm.



Drawer with dimension 830x550 with internal useful height of 130 mm.



Slides with static load up to 60 Kg.



Steel sheet handle.









RESISTANCE AND STABILITY

Made in Italy



GALVANIZED STEEL 3 mm THICKNESS

Laser cutting with hand finishing on edges.

MULTILAYER WOODEN WORKTOP 30 mm THICKNESS

Beech and poplar plywood to provide resistance and lightness.



METAL SHEET LEGS WITH THICKNESS 1.2 mm


Side holes to fix several workbenches side by side. Metal sheet legs with holes for floor fixing.

WORKBENCHES 506 TL

WITH WOODEN WORKTOP









Multilayer wooden worktop 30 mm thickness.

506 TL 005060046





Workbench with wooden worktop

- Multilayer wooden worktop 30 mm thickness.
- Worktop material: internal layers in fir, external layers in ash tree.
- Metal sheet legs and bottom shelf 1,2 mm thickness.
- Structure painted in colour black RAL 9005.
- · Side holes to fix several workbenches side by side.
- · Arranged for ground fixing.
- 6 legs for 2 meters lenght model.
- Possibility to assemble the drawer 506 TC1.
- Static load resistance: 2000 kg.
- Space in between legs: 864 mm.
- Space in between bottom shelf and worktop: 570 mm.







Drawer with dimension 830x550 with internal useful height of 130 mm.



Slides with static load up to 60 Kg.



Steel sheet handle.

506 TLC





Workbench with wooden worktop - 2 drawers

- 2 drawers included with internal dimensions 834x550x130 mm.
- Drawers mounted on telescopic slides with static load up to 60 Kg.
- Multilayer wooden worktop 30 mm thickness.
- Worktop material: internal layers in fir, external layers in ash tree.
- Metal sheet legs and bottom shelf 1,2 mm thickness.
- Structure painted in colour black RAL 9005.
- Side holes to fix several workbenches side by side.
- · Arranged for ground fixing.
- 6 legs for 2 meters lenght model.
- Possibility to assemble the drawer 506 TC1.
- Static load resistance: 2000 kg.
- Space in between legs: 864 mm.
- Space in between bottom shelf and worktop: 570 mm.









DRAWER 506 TC1

FOR WORKBENCH 506 TA AND 506 TL



506 TC1 U050601540






Drawer for workbench

- Compatible with workbenches 506 TA and TL with lenght 2 meters.
- Internal dimensions: 830x550 mm.
- Useful internal height: 130 mm.
- Steel sheet handle.
- Telescopic slides with static load resistance up to 60 Kg.
- Lock with keys included.
- Steel sheet structure painted in black RAL 9005.





Drawer with dimension 830x550 with internal useful height of 130 mm.



Telescopic slides with static load up to 60 Kg.



Lock with keys included.



Steel sheet handle.

Made in Italy





Handle made in tubolar steel 25 mm diameter.



Each shelf is covered by and ABS mat 2 mm thickness.



Oil-proof rubber wheels (Ø 100 mm).





Utility chart

- 3 shelves of 770x448 mm.
- Each shelf is covered by and ABS mat 2 mm thickness.
- · Side edges of 37 mm on each shelf.
- Handle made in tubolar steel 25 mm diameter.
- Two swivelling and two fixed wheels (Ø 100 mm), one with brake.
- · Supplied disassembled.
- Maximum loading capacity: 200 Kg.
- Structure painted in colour red RAL 3020.





Do you need support from us?Go to our website:







Stanley Black & Decker Italia S.r.l.

Via Volta, 3 - 21020 - Monvalle (VA) Tel. +39 0332 790 111 - info.mv@usag.it

usag-tools.net

